

PROMURA

DESCRIPTION:

GripKote 300 is a multi-purpose water based bitumen emulsion that provides a quick and economical method of applying a waterproofing membrane that is non-hazardous, non-toxic and odour-free.

USES:

- Retaining walls
- Protection of metal roofs, gutters and downpipes
- Protection of most timber products, such as fence posts
- Horticulture - to seal pruning cuts and grafts
- Concrete surfaces and rendering

SURFACE PREPARATION

All surfaces must be clean, dry and free from any loose materials such as paint, oils and rust.

APPLICATION:

Before use stir contents of **GripKote 300** thoroughly. Apply two coats by brush, roller, trowel or high-pressure airless spray gun at approximately 1 sq m per litre per coat. Allow first coat to fully dry before applying 2nd coat. Drying time 4 - 24 hours depending on drying conditions.

COVERAGE:

Approx 1 sq m per litre per coat depending on surface

GripKote 300

PRECAUTIONS:

Do not apply below 5°C, where hydrostatic pressure exists or when damp conditions may prevent the emulsion from drying out. Affected by oils, solvents and some detergents.

Where **GripKote 300** is to be left exposed to sunlight it should be painted with an acrylic paint to prevent breakdown caused by ultra violet attack. (Allow at least six weeks before painting.)

Maximum thickness of a single coat must not exceed 1mm.

When applied to timber, old surfaces should be sanded down to provide an even flat surface.

When using **GripKote 300** to waterproof retaining walls etc, ensure the membrane is covered with fibreboard or a similar material to prevent piercing of the membrane.

PACKAGING:

Available in 1 litre, 4 litre and 20 litre containers

CLEAN UP:

Use cold water when wet, mineral turps when material is dry.

STORAGE:

Do not allow containers to freeze. May be stored for 24 months in a sealed container under cover between 5°C and 40°C. For long term storage of partly used containers, level off contents of containers and cover surface with five centimetres of water and replace lid tightly. Before reusing **GripKote 300** pour off excess water and stir emulsion thoroughly.

UES Promura 10 - 12 McWilliam Street Springvale Vic 3171
Tel: 03 9547 5833 Fax: 03 9548 1537
sales@uespromura.com.au www.uespromura.com.au