All purpose band

- Easy to form around any section
- Flame retardant Low Smoke PPA coating
- Thick coating - kind to hands / cable
- Simple fastening with nuts, bolts, screws
- Three widths available
- 316 Stainless steel or galvanised carbon steel



Coated band

- Flame retardant, Low Smoke PPA coating
- Thick coating kind to hands / cable
- 316 or 304 Type Stainless Steel





Bantam Tool C075
For application of coated band.
See page 14 for details

BAND-IT All Purpose Band

Metal thickness 0.030 (0.75mm) Coated thickness 0.050 (1.3mm)

Cat. No.	Width* In.	Width* mm	Length Ft.	Length M	Weight Lbs	Weight Kg	Hole Diameter In	Hole Diameter mm
Type 316 Stainless Steel (PPA571 Coated)								
AE465	1/2	12	33.0	10	1.2	0.6	3/16	5
AE466	3/4	17	33.0	10	2.1	1.0	9/32	7
AE467	1	26	33.0	10	2.9	1.3	5/16	8
AE475	1/2	12	82.5	25	3.1	1.4	3/16	5
AE476	3/4	17	82.5	25	5.3	2.4	9/32	7
AE477	1	26	82.5	25	7.3	3.3	5/16	8
AB465	1/2	12	9.9	3	0.4	0.2	3/16	5
AB466	3/4	17	9.9	3	0.4	0.2	9/32	7
Type 316 Stainless Steel (Uncoated)								
AE405	1/2	12	33.0	10	1.2	0.6	3/16	5
AE406	3/4	17	33.0	10	1.9	0.9	9/32	7
AE407	1	26	33.0	10	2.2	1.0	5/16	8
AE425	1/2	12	82.5	25	3.1	1.4	3/16	5
AE426	3/4	17	82.5	25	4.6	2.1	9/32	7
AE427	1	26	82.5	25	5.5	2.5	5/16	8
AB405	1/2	12	9.9	3	0.4	0.2	3/16	5
AB406	3/4	17	9.9	3	0.4	0.2	9/32	7
Galvanised Carbon Steel (PPA 571 Coated)								
AE565	1/2	12	33.0	10	1.2	0.6	3/16	5
AE566	3/4	17	33.0	10	2.0	0.9	9/32	7
AE567	1	26	33.0	10	4.0	1.8	5/16	8
AE575	1/2	12	82.5	25	3.1	1.4	3/16	5
AE576	3/4	17	82.5	25	5.3	2.4	9/32	7
AE577	1	26	82.5	25	9.9	4.5	5/16	8
AB565	1/2	12	9.90	3	0.4	0.2	3/16	5
AB566	3/4	17	9.90	3	0.4	0.2	9/32	7
Galvanised Carbon Steel (Uncoated)								
AE505	1/2	12	33.0	10	1.2	0.6	3/16	5
AE506	3/4	17	33.0	10	2.0	0.9	9/32	7
AE507	1	26	33.0	10	4.0	1.8	5/16	8

* Width can vary depending on coating thickness

316 SS only

316 and 201 Stainless Steel Band

PPA 571 Coated Pkg. Qty. 1

316SS Cat No.	201SS Cat No.	Width In.	Width mm	Length Ft.	Length M	Weight Lbs	Weight Kg
AE432		1/4	6.35	82.5	25	2.0	0.9
AE433	AE933	3/8	9.53	82.5	25	2.6	1.2
AE434	AE934	1/2	12.70	82.5	25	3.5	1.6
AE435	AE935	5/8	15.88	82.5	25	4.4	2.0
AE436	AE936	3/4	19.05	82.5	25	5.3	2.4

Approximate thickness = 0.048" (1.22mm), when coated

316 Stainless Steel Band

Uncoated Pkg. Qty. 1

Cat. No.	Width In.	Width mm	Length Ft.	Length M	Weight Lbs	Weight Kg
AE442	1/4	6.35	82.5	25	2.0	0.9
AE443	3/8	9.53	82.5	25	2.6	1.2
AE444	1/2	12.70	82.5	25	3.5	1.6
AE445	5/8	15.88	82.5	25	4.4	2.0
AE446	3/4	19.05	82.5	25	5.3	2.4

Thickness = 0.016" (0.406mm)

Clips Uncoated

Type 316 Stainless Steel Pkg. Qty. 100

Cat. No.	Width In.	Width mm	Weight Lbs	Weight Kg
AE452	1/4	6.35	0.3	0.1
AE453	3/8	9.53	0.6	0.3
AE454	1/2	12.70	1.0	0.4
AE455	5/8	15.88	1.1	0.5
AE456	3/4	19.05	1.3	0.6

Coated clips are available - price on request



UES Promura - Product enquiries

+61 3 9547 5833 | sales@uespromura.com.au | uespromura.com.au

10-12 McWilliam Street, Springvale VIC 3171, Australia

BAND-IT Ties

- Re-useable
- Low Smoke, Zero Halogen, PPA Coated
- Tension by hand or application Tool
- 316 Stainless steel
- For cable bundling in harsh environments
- Thick coating protects cable/hands
- Vibration proof





BAND-IT Ties Coated with PPA Pkg. Qty. - 100

Cat. No.	Max Bundle Dia		Width		Length		Weight	
	In.	*mm*	*In.*	*mm*	*In.*	*mm*	*Lbs*	*Kg*
AE111	1.5	38	1/4	6.35	6	152	1.4	0.6
AE112	2.5	63	1/4	6.35	9	229	1.8	0.8
AE113	3.4	86	1/4	6.35	12	305	2.1	1.0
AE114	5.4	137	1/4	6.35	18	457	3.0	1.4
AE115	7.3	185	1/4	6.35	24	610	3.7	1.7
AE311	1.5	38	3/8	9.53	6	152	1.8	0.8
AE312	2.5	63	3/8	9.53	9	229	2.5	1.1
AE313	3.4	86	3/8	9.53	12	305	3.1	1.4
AE314	5.4	137	3/8	9.53	18	457	4.4	2.0
AE315	7.3	185	3/8	9.53	24	610	6.6	3.0
AE316	9.1	231	3/8	9.53	30	762	7.0	3.2
AE317	11.0	280	3/8	9.53	36	914	8.3	3.8

Note: metal thickness .015" (.38mm) approximate coated thickness = .040"(1.0mm)
Standard colour Black other colours available on request



BAND-IT Ties - Uncoated Pkg. Qty. - 100

Cat. No.	Max Bundle Dia		Width		Length		Weight	
	In.	*mm*	*In.*	*mm*	*In.*	*mm*	*Lbs*	*Kg*
AE101	1.5	38	1/4	6.35	6	152	1.4	0.6
AE102	2.5	63	1/4	6.35	9	229	1.8	0.8
AE103	3.4	86	1/4	6.35	12	305	2.1	1.0
AE104	5.4	137	1/4	6.35	18	457	3.0	1.4
AE105	7.3	185	1/4	6.35	24	610	3.7	1.7
AE301	1.5	38	3/8	9.53	6	152	1.8	0.8
AE302	2.5	63	3/8	9.53	9	229	2.5	1.1
AE303	3.4	86	3/8	9.53	12	305	3.1	1.4
AE304	5.4	137	3/8	9.53	18	457	4.4	2.0
AE305	7.3	185	3/8	9.53	24	610	6.6	3.0
AE306	9.1	231	3/8	9.53	30	762	7.0	3.2
AE307	11.0	280	3/8	9.53	36	914	8.3	3.8



C075 Bantam Tool



AE200 Cable Tie Tensioner



AE201 Tensioning Hook

Application Tools Pkg. Qty. - 1

Cat. No.	Description	Weight	
		Lbs.	*Kgs.*
C075	For tensioning and cutting BAND-IT Ties and Coated Band. 3 way handle position for pistol grip or two hand operation	2.6	1.20
AE200	For tensioning BAND-IT Ties and Multi-Lok Ties (No cut off)	0.6	0.30
AE201	For tensioning BAND-IT Ties and Multi-Lok Ties (No cut off)	0.1	0.05

Multi-Lok Ties

- Self Locking
- Flame retardant
- U.V. and corrosion resistant
- Applied by hand or M503, KE922, AE200 and AE201 tools
- Tensile Strength > 90 Kg.
- Coated in Nylon 11 For greater corrosion resistance
- Excellent minimum loop tensile strength. In excess of 890N (7mm wide) and 1112N (12mm wide) for both coated and uncoated versions





Multi-Lok Ties Coated Pkg. Qty 100

Type 316 Stainless Steel Coated with Nylon 11

Cat. No.	Maximum Bundle Dia		Width		Length		Weight	
	In.	*mm*	*In.*	*mm*	*In.*	*mm*	*Lbs.*	*Kg.*
AE611	1.3	33	0.28	7	6	150	0.66	0.30
AE612	2.2	57	0.28	7	9	225	0.99	0.45
AE613	3.2	81	0.28	7	12	300	1.32	0.60
AE614	5.1	129	0.28	7	18	450	1.76	0.80
AE615	7.1	180	0.28	7	24	610	2.64	1.20
AE711	1.3	33	0.47	12	6	150	1.10	0.50
AE712	2.2	57	0.47	12	9	225	1.65	0.75
AE713	3.2	81	0.47	12	12	300	2.20	1.00
AE714	5.1	129	0.47	12	18	450	2.97	1.35
AE715	7.1	180	0.47	12	24	610	4.29	1.95



Multi-Lok Ties Uncoated Pkg. Qty 100

Type 316 Stainless Steel Uncoated

Cat. No.	Maximum Bundle Dia		Width		Length		Weight	
	In.	*mm*	*In.*	*mm*	*In.*	*mm*	*Lbs.*	*Kg.*
AE601	1.9	48	0.28	7	6	150	0.66	0.30
AE602	2.8	71	0.28	7	9	225	0.81	0.40
AE603	3.8	96	0.28	7	12	300	1.21	0.55
AE604	5.7	144	0.28	7	18	450	1.98	0.90
AE605	7.6	193	0.28	7	24	610	2.64	1.20
AE701	1.9	48	0.47	12	6	150	1.10	0.50
AE702	2.8	71	0.47	12	9	225	1.65	0.75
AE703	3.8	96	0.47	12	12	300	2.20	1.00
AE704	5.7	144	0.47	12	18	450	3.19	1.45
AE705	7.6	193	0.47	12	24	610	4.29	1.95

Application Tools



M503 Multi-Lok tool with adjustable tension and automatic cut off weight 0.94Lbs. (.43Kg.)



KE922 Manual Tensioning tool with cut off lever Weight 1.25Lbs. (.57Kg.)



AE200 Tensioner
See page 14 for details



AE201 Tensioning Hook
See page 14 for details

Ball-Lok Ties

- Improved tensile strength
- Available in 316 or 304 Stainless Steel
- 316SSties also available fully coated in Epoxy
- Self locking for speedy application
- Smooth Internal Diameter
- Install by hand or with K502, KE922 tools







K502 Ball-Lok Tool with adjustable Tension and automatic cut off Weight .94Lbs (.43Kg)

304 and 316 Stainless Steel

Package Quantity 100

Uncoated

Cat. No. 304 SS	Cat No. 316 SS	Maximum Bundle Diameter in	Maximum Bundle Diameter mm	Approximate Length in	Approximate Length mm	Approximate Width in	Approximate Width mm	Approximate Weight Lbs.	Approximate Weight Kg.	Min. Loop Tensile Strength Lbs	Min. Loop Tensile Strength N
KE1118	KE0118	1.2	30	5.9	150	0.18	4.6	0.42	0.19	200	890
KE1128	KE0128	2.0	50	7.9	201	0.18	4.6	0.57	0.26	200	890
KE1138	KE0138	2.7	69	10.2	259	0.18	4.6	0.70	0.32	200	890
KE1148	KE0148	4.0	102	14.2	360	0.18	4.6	0.92	0.42	200	890
KE1158	KE0158	6.0	152	20.4	520	0.18	4.6	1.32	0.60	200	890
KE1168	KE0168	8.0	203	26.8	679	0.18	4.6	1.76	0.80	200	890
KE1178	KE0178	10.0	254	33.0	838	0.18	4.6	2.07	0.94	200	890
KE1188	KE0188	12.0	305	42.0	1067	0.18	4.6	2.38	1.08	200	890
KE1328	KE0328	2.0	50	7.9	201	0.31	7.9	0.99	0.45	300	1335
KE1338	KE0338	2.7	69	10.2	259	0.31	7.9	1.32	0.60	300	1335
KE1348	KE0348	4.0	102	14.2	360	0.31	7.9	1.67	0.76	300	1335
KE1358	KE0358	6.0	152	20.4	520	0.31	7.9	2.23	1.04	300	1335
KE1368	KE0368	8.0	203	26.8	679	0.31	7.9	2.86	1.30	300	1335
KE1378	KE0378	10.0	254	33.0	838	0.31	7.9	3.52	1.60	300	1335
KE1388	KE0388	12.0	305	42.0	1067	0.31	7.9	4.62	2.10	300	1335





KE922 Manual Tensioning Tool with tail cut-off lever Weight 1.25Lbs (.57Kg)

316 Stainless Steel

Package Quantity 100

Epoxy Coated

Cat. No.	Max.Bundle Diameter in	Max.Bundle Diameter mm	Approximate Length in	Approximate Length mm	Approximate Width in	Approximate Width mm	Approximate Weight Lbs.	Approximate Weight Kg.	Min. Loop Tensile Strength Lbs	Min. Loop Tensile Strength N
KE0228	2.0	50	7.9	201	0.18	4.6	0.62	0.28	150	668
KE0238	2.7	69	10.2	259	0.18	4.6	0.75	0.34	150	668
KE0248	4.0	102	14.2	360	0.18	4.6	1.01	0.46	150	668
KE0258	6.0	152	20.4	520	0.18	4.6	1.41	0.64	150	668
KE0268	8.0	203	26.8	679	0.18	4.6	1.80	0.82	150	668
KE0278	10.0	254	33.0	838	0.18	4.6	2.33	1.06	150	668
KE0428	2.0	50	7.9	201	0.31	8.0	1.16	0.53	250	1112
KE0438	2.7	69	10.2	259	0.31	8.0	1.50	0.68	250	1112
KE0448	4.0	102	14.2	360	0.31	8.0	1.78	0.81	250	1112
KE0458	6.0	152	20.4	520	0.31	8.0	2.46	1.12	250	1112
KE0468	8.0	203	26.8	679	0.31	8.0	3.17	1.44	250	1112
KE0478	10.0	254	33.0	838	0.31	8.0	3.83	1.74	250	1112

Custom Length Ball-Lok Banding System

Available in both 304 and 316 Stainless steel.

2 widths 0.18"(4.6mm) and .31"(7.9mm).

Apply by hand or use the K502 or KE922 tools

For further details please contact sales desk

Bands and Heads

Part No.	Width mm	Pack Type	Material
CE1569	7.9	100m reel	304 S. Steel
CE4569	7.9	100m reel	316 S. Steel
CB1569	7.9	Box of 1000	316 S. Steel
CE3569	4.6	100m reel	304 S. Steel
CE2569	4.6	100m reel	316 S. Steel
CB2569	4.6	Box of 1000	316 S. Steel



Band: 100m per Reel
CE3569, CE2569
CE1569, CE4569



Heads: Box of 1000
CB1569, CB2569

Tie-Lok Ties

- Low Profile, Small head
- No slip back - Dual lock
- Minimum Loop Tensile Strength:-
  Mini Tie-Lok - 100 Lbs (445N)
  Tie-Lok - 200 Lbs (890N)
  Ultra-Lok - 400Lbs (1776N)



Smooth I.D. Tie-Lok Ties

Pkg. Qty. 100

Stainless Steel Thickness .015" (.38mm) Band width 0.25" (6.35mm)

304SS Cat. No.	316SS Cat.No.	Max. Bundle Dia.		Length		Weight	
		Ins.	*mm*	*In.*	*mm*	*Lbs.*	*Kg.*
AS211	AS411	2	51	10.0	254	1.2	0.54
AS212	AS412	4	101	16.5	419	1.8	0.86
AS213	AS413	6	152	22.5	572	2.6	1.17
AS214	AS414	8	203	29.0	737	3.3	1.50
AS215	AS415	10	254	35.0	889	3.9	1.79

0.38"(9.53 mm) wide version available on special order. Contact our Sales Desk.





IT1000



A920

Smooth I.D. Mini Tie-Lok Ties

Pkg. Qty. 100

Stainless Steel Thickness .015" (.38mm) Band width 0.177" (4.5mm)

304SS Cat. No.	316SS Cat.No.	Max. Bundle Dia.		Length		Weight	
		In.	*mm*	*In.*	*mm*	*Lbs.*	*Kg.*
AS221	AS421	1	25	6.5	165	0.7	0.30
AS222	AS422	2	51	10.0	254	0.9	0.40
AS223	AS423	4	102	16.0	406	1.4	0.61
AS224	AS424	6	152	22.5	572	1.9	0.84
AS225	AS425	8	203	29.0	737	2.4	1.06





IT0750



A910

Smooth I.D. Ultra-Lok Ties

Pkg. Qty. 100

Austenitic Stainless Steel Band Width 0.25" (6.35mm)

Cat. No.	Max. Bundle Dia.		Length		Weight	
	In.	*mm*	*In.*	*mm*	*Lbs.*	*Kg.*
AU202	1.5	38.1	8.0	203	1.0	0.45
AU203	2.5	63.5	10.0	254	1.2	0.54
AU204	3.0	76.2	12.0	305	1.4	0.64
AU205	3.8	96.5	14.0	356	1.6	0.74
AU206	4.5	114.3	16.0	406	1.9	0.86
AU207	5.4	137.2	19.0	483	2.2	1.00
AU208	7.0	177.8	24.0	610	2.7	1.22
AU209	8.5	215.9	29.0	737	3.2	1.46
AU215	10.5	266.7	35.0	889	3.9	1.75





IT3000



A940

Smooth I.D. Universal Clamps

Pkg. Qty. 100

Austenitic Stainless Steel

Thickness .015" (.38mm) Width 0.25" (6.35mm)

Cat. No.	Maximum Bundle Dia.		Weight	
	In.	*mm*	*Lbs.*	*Kgs.*
JU242	1.0	25	1.2	0.54
JU252	1.5	38	1.4	0.64
JU253	2.0	51	1.7	0.77
JU254	2.5	64	1.9	0.86
JU256	3.0	75	2.2	1.00
JU257	3.5	89	2.4	1.09
JU258	4.0	102	2.6	1.18
JU259	4.5	114	2.7	1.23

Pneumatic Tools IT1000 or IT3000





A940



A920

Hand Tools

Cat. No.	Description	Weight	
		Lbs.	*Kg.*
A920	Tie-Lok II Tool for Tie-Lok and Universal Clamps	0.94	0.43
A910	Mini Tie-Lok Tool for Mini Tie- Lok Ties	0.94	0.43
A940	Ultra-Lok Tool for Ultra-Lok Ties, Tie-Lok Ties, Universal Clamps	0.94	0.43

Pneumatic Tools

Cat. No.	Description	Weight	
		Lbs.	*Kgs.*
IT1000	Pneumatic Tool for all 1/4" (6.35mm) Tie-Lok and Universal Bands/Clamps.	10.4	4.70
IT0750	Pneumatic Tool for all 0.177"(4.5mm) Mini Tie-Lok Ties.	10.4	4.70
IT3000	Pneumatic Tool for all 1/4" (6.35mm) Ultra-Lok and Tie-Lok Bands/Clamps.	10.4	4.70
IT6000	Pneumatic Tool for all 3/8" (9.5mm) Tie-Lok Ties.	10.4	4.70
I17490	Bench Mounting and Foot Control Kit.	1.4	0.63
A320	Pneumatic Tool Locator allows installation of clamp a constant distance from reference surface.	0.4	0.20



IT1000
IT0750,
IT3000,
IT6000

Tie-Dex Clamping System

- EMI, RFI Shield termination
- Patented
- No welding, heating or crimping
- Low profile design
- Manual or Pneumatic tooling
- Calibrated application tools
- Military specifications applicable
  Environmental MIL Standard 810C/810A, MIL-C-38999H
  Electrical details on request
  Mechanical MIL-C-85049, MIL-STD-1344, MILSTD-1344A, MIL Standard 901C



Tie-Dex Bands and Tie-Dex Micro Bands provide a permanent shield termination for any size and type of backshell design.



Tie-Dex (Flat)

Tie-Dex Band

Type 304 Stainless Steel .020" (.51mm) Thickness x .24" (6.1mm) Wide

Cat. No.	Description	Pkg. Type	Qty. per Pack	Length In.	Length mm	Weight Lbs.	Weight Kg.
A10088	Coiled and Individually Bagged	Box	100	14.25	362	2.05	0.93
A10089	Flat and bagged	Bag	100	14.25	362	2.05	0.93
A11089	Flat and bagged	Bag	100	18.00	457	2.52	1.10



Tie-Dex (Coiled double wrap)

Tie-Dex II Tool

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A40199	Pre-calibrated Hand Tool	1	1.20	0.550
A44699	Calibration Key	1	0.15	0.070
A40699	Replacement Part - Cut-off Blade Kit	1	0.01	0.005



A40199 Tie-Dex II Hand Tool

Tie-Dex II Pneumatic Tool

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A35199	Pneumatic Tool to apply 0.24" (6.1mm) Tie-Dex Bands	1	5.26	2.370
A40699	Replacement Part Cut-off Blade Kit	1	0.02	0.010
A40787	Cut-off knife	1	0.01	0.005



A35199 Tie-Dex II Pneumatic Tool
A35599 Tie-Dex II Micro Pneumatic Tool

Tie-Dex II Tool/Gauge Kit

(see page 19)

A49099	0.24" (6.1mm) Kit, Tie-Dex II Tool/gauge	1	4.60	2.12

Tie-Dex Gauge

A48599	0.24" (6.1mm) Tension Gauge	1	1.00	0.45

Accessories for Tie-Dex II and Tie-Dex Micro pneumatic tools

Tie-Dex II Pneumatic Bench Mount/Foot Control Kit

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A37099	Mounts Pneumatic Tool to work bench. Foot control allows hands-free operation	1	1.40	0.63

Tie-Dex II Pneumatic Tool Locator

A32099	Allows Clamps to be installed same distance from reference surface	1	4.60	2.12

Tie-Dex Clamping System

- EMI, RFI Shield termination
- Patented
- No welding, heating or crimping
- Low profile design
- Manual or Pneumatic tooling
- Calibrated application tools
- Military specifications applicable
  Environmental MIL Standard 810C/810A, MIL-C-38999H
  Electrical details on request
  Mechanical MIL-C-85049, MIL-STD-1344, MILSTD-1344A, MIL Standard 901C



Tie-Dex Bands and Tie-Dex Micro Bands provide a permanent shield termination for any size and type of back-shell design.



Tie-Dex (Flat)

Tie-Dex Micro Band

Type 304 Stainless Steel .015" (.38mm) Thickness x .12" (3.05mm) wide

Cat. No.	Description	Pkg. Type.	Qty. per Pack	Length In.	Length mm	Weight Lbs.	Weight Kg.
A31188	Coiled and individually bagged	Box	100	8.125	207	0.43	0.20
A31189	Flat and bagged	Bag	100	8.125	207	0.43	0.20
A31089	Flat and bagged	Bag	100	14.250	362	0.71	0.32



Tie-Dex
(Coiled double wrap)

Tie-Dex II Micro Tool

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A30199	Pre-calibrated Hand Tool to install Micro Band	1	1.20	0.550
A46799	Replacement part - Cut off blade Kit	1	0.01	0.005
A35599	Pneumatic tool to apply Tie-Dex Micro Bands See page 18	1	5.26	2.370



A30199 Tie-Dex II
Micro Tool

Tie-Dex Micro Tool/Gauge Kit

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A59099	Kit- Tie-Dex II Tool/Gauge	1	4.60	2.12

Tie-Dex Micro Gauge

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A47599	Tension Gauge	1	1.00	0.45



A49099 Tie-Dex II
Tool/Gauge Kit

A59099 Tie-Dex II
Micro Tool/Gauge Kit

Accessories for Tie-Dex II and Tie-Dex Micro pneumatic tools

Tie-Dex Calibration Kit

Use with all Tie-Dex tools

Cat. No.	Description	Qty. per Pack	Weight Lbs	Weight Kg.
A50099	Contents: Calibration device, tool mounting bracket for all 3 tools, Test band, Hex key for bracket removal , Calibration key, Carrying case.	1	4.30	2.00
A50599	Replacement Tie-Dex Test Band	50	0.33	0.15
A50699	Replacement Micro Tie-Dex Test Band	50	0.13	0.06



A50099 Tie-Dex
Calibration Kit

Tie-Dex Calibration Device

Use with all Tie-Dex tools

A50189	Calibration Device	1	1.18	0.53

Identification Tags and Embossing System

I.D Tag Imprinter

Pkg. Qty. 1

Cat. No.	Description	Weight Lbs.	Weight Kg.
ID200	I.D. Tag Imprinter with 3/32" (2.38mm) Character Wheel	29.5	13.4
ID202	I.D. Tag Imprinter with 1/16" (1.59mm) Character Wheel	29.5	13.4
ID203	I.D. Tag Imprinter with 1/8" (3.18mm) Character Wheel	29.5	13.4
ID204	I.D. Tag Imprinter with 3/16" (4.76mm) Character Wheel	29.5	13.4



I.D. Tag Imprinter

I.D Kit

Pkg. Qty. 1

Cat. No.	Description	Weight Lbs.	Weight Kg.
ID300	Handy Kit contains: One Tie-Lok Tool plus 200 pcs. I.D. Tags 3/4" x 2" (19.05 x 51mm) 100 pcs. I.D. Tags 11/2" x 21/2" (38.1 x 63mm) 100 pcs. I.D. Tags 3/4" x 31/2" (19.05 x 89mm) 100 pcs. Tie-Loks 1/4" x 10" (6.35 x 254mm) 200 pcs. Tie-Loks 1/4" x 16.5" (6.35 x 419mm) 100 pcs. Tie-Loks 1/4" x 22.5" (6.35 x 572mm)	21.5	9.80



I.D. Kit

I.D. Band Guide Kit

Pkg. Qty. 1

Cat. No	Description	Weight Lbs.	Weight Kg.
ID285	Fixture to imprint directly onto Tie-Lok Tie	0.50	0.20

I.D. Letter Dial Kit

Pkg. Qty. 1

Cat. No.	Description	Weight Lbs.	Weight Kg.
ID290	3/32" (2.38mm) Letter Dial Kit	2.09	0.95
ID281	1/16" (1.59mm) Letter Dial Kit	2.09	0.95
ID282	1/8" (3.18mm) Letter Dial Kit	2.09	0.95
ID283	3/16" (4.76mm) Letter Dial Kit	2.09	0.95
ID284	1/4" (6.35mm) Letter Dial Kit	2.09	0.95

I.D. Tags

Pkg. Qty. 100

304SS Cat.No.	316SS Cat.No.	Thickness In.	Thickness mm	Width In.	Width mm	Length In.	Length Mm	Weight Lbs.	Weight Kg.
ID 100	ID440	0.010	0.254	0.75	19.05	2.0	51	0.5	0.22
ID 101	ID441	0.015	0.381	1.50	38.10	2.5	63	1.2	0.55
ID 102	ID442	0.015	0.381	0.75	19.05	3.5	89	0.8	0.36

I.D. Tags



ID102, ID442



ID100, ID440

ID101, ID441

Customised Embossed Tags

Pkg. Qty. 1

Cat. No.	Width In.	Width mm	Thickness In.	Thickness mm	No. of Characters
AE487	0.39	10	0.01	0.25	1-10
AE488	0.39	10	0.01	0.25	11-20

Customised Embossed Tags



S.S. Tape Embossing System

Pkg. Qty. 1

Cat. No.	Description	Weight Lbs	Weight Kg
ID400	Hand-held tool for embossing S.S. ID Tape	2.57	1.17
ID405	S.S. Tape, Width:1/2" (12.7mm), Thickness: 0.005" (0.127mm) Length: 20' (6m)	0.18	0.01





ID400 Embossing Tool



ID405 Replacement tape 1/2" (12.7mm) wide

Fasten embossed tape with Ball-Lok or Tie-Lok ties

EASY READ I.D. System

- A complete range of letters, numbers and symbols
- Made from 316 Stainless Steel
- Easy to read in dim light
- Fits over Easy Strips or carriers
- Slide them directly onto cable ties
- Fasten strips and carriers to pipes and cables with cable ties



Easy Carrier can be applied using Tie-Lok Ties, Ball-Lok Ties, or Multi-Lok Ties.

EASY READ Characters

Pkg. Qty. 100

Type 316 Stainless Steel

Cat. No.	Description/Order No.	Weight Lbs.	Weight Kg.
AE010	EASY A	0.31	0.14
AE011	EASY B	0.31	0.14
AE012	EASY C	0.31	0.14
AE013	EASY D	0.31	0.14
AE014	EASY E	0.31	0.14
AE015	EASY F	0.31	0.14
AE016	EASY G	0.31	0.14
AE017	EASY H	0.31	0.14
AE018	EASY I	0.31	0.14
AE019	EASY J	0.31	0.14
AE020	EASY K	0.31	0.14
AE021	EASY L	0.31	0.14
AE022	EASY M	0.31	0.14
AE023	EASY N	0.31	0.14
AE024	EASY O	0.31	0.14
AE025	EASY P	0.31	0.14
AE026	EASY Q	0.31	0.14
AE027	EASY R	0.31	0.14
AE028	EASY S	0.31	0.14
AE029	EASY T	0.31	0.14
AE030	EASY U	0.31	0.14
AE031	EASY V	0.31	0.14
AE022	EASY W	0.31	0.14
AE032	EASY X	0.31	0.14
AE033	EASY Y	0.31	0.14
AE034	EASY Z	0.31	0.14
AE018	EASY 1	0.31	0.14
AE037	EASY 2	0.31	0.14
AE038	EASY 3	0.31	0.14
AE039	EASY 4	0.31	0.14
AE040	EASY 5	0.31	0.14
AE041	EASY 6	0.31	0.14
AE021	EASY 7	0.31	0.14
AE042	EASY 8	0.31	0.14
AE041	EASY 9	0.31	0.14
AE024	EASY 0	0.31	0.14
AE035	EASY MINUS/HYPHEN -	0.31	0.14
AE036	EASY BLANK	0.31	0.14
AE046	EASY PLUS +	0.31	0.14
AE047	EASY EARTH	0.31	0.14
AE048	EASY SINE	0.31	0.14
AE049	EASY SLASH/	0.31	0.14
AE053	ARROW	0.31	0.14



EASY READ characters threaded onto Multi-Lok and BAND-IT Cable Ties



Easy Strip applied with Multi-Lok ties



EASY READ Characters and Easy Carrier



Flag Tag created with Tie-Lok threaded through hole in Easy Carrier

EASY READ Carriers

Pkg. Qty. 100

Cat. No.	Description/Order No.	Width In.	Width mm	Length In.	Length mm	Weight Lbs.	Weight Kg.
AE043	EASY CARRIER 6	0.38	9.53	3.64	92.5	0.73	0.33
AE044	EASY CARRIER 10	0.38	9.53	5.14	130.6	1.25	0.56
AE045	EASY CARRIER 16	0.38	9.53	7.39	187.7	1.47	0.66
AE050	EASY STRIP Short	0.38	9.53	4.25	108.0	0.98	0.44
AE051	EASY STRIP Medium	0.38	9.53	5.75	146.0	1.33	0.60
AE052	EASY STRIP Long	0.38	9.53	8.00	203.2	1.85	0.83

EASY READ Kit

Pkg. Qty. 1

Cat. No.	Description/Order No.	Weight Lbs.	Weight Kg.
AE060	EASY READ Kit - Contains 50 of each character/carrier/strip	5.60	2.54



AE060 EASY READ Kit